

Rogue ET 200iP PRO

Portable solutions for professional welding



Rogue ET 200iP PRO

Industry

- Food & beverage
- Repair and Maintenance
- Civil Construction
- Agricultural Equipment
- Industrial and General Fabrication

Rogue ET 200iP Pro is a powerful high frequency start TIG machine. This easy to use welder is designed with a robust and durable housing that is IP23S rated. Weighing only 9.6 kg (21.2 lbs) this lightweight welder features an ergonomic handle, carrying strap and long extension cables for maximum portability.

Rogue ET offers exceptional arc characteristics, both in TIG and Stick mode. Want more control over your welder? Rogue ET provides several TIG parameters that can be easily adjusted including gas pre flow, start current, ramp up time, ramp down time, finish current and post flow. All of which can be programmed using 2 or 4 stroke mode for greater arc control. Additionally, Rogue ET 200iP PRO offers a pulse feature with background current control and frequency adjustments up to 500 Hz for better heat input control. In Stick mode, Hot Start or Arc Force can be adjusted according to individual welding preferences or applications.

- Excellent high frequency TIG start ensures no failures on ignition with superior arc characteristics for smooth and stable performance
- Easy to Use – set the welding current and weld with excellent result, also suitable for use with compliant generators
- Robust Housing – IP23S designed for both fabrication floor or site applications
- Advanced TIG parameter control to match every application and pulse feature up to 500 Hz for better heat input control
- Power Factor Correction (PFC) – ensures a stable arc, resistant to power fluctuations even while working on long extension cables up to 100 m (328 ft)
- Compatible with current adjusting foot pedal (sold separately)

Visit esab.com for more information.



Control panel

Rogue ET 200iP PRO

Specifications	
	ET 200iP PRO
Primary Voltage 1 ph	115/230 VAC ± 15%, 1 ph, 50/60 Hz
Maximum Output	200 A
Rated kVA	7 kVA
Energy Save Mode	50 W
Open Circuit Voltage	78 V DC
Stick Welding Output @ 25% Duty Cycle @ 60% Duty Cycle @ 100% Duty Cycle	200 A / 28.0 V 129 A / 25.2 V 100 A / 24.0 V
TIG Welding Output @ 25% Duty Cycle @ 60% Duty Cycle @ 100% Duty Cycle	200 A / 18.0 V 129 A / 15.2 V 100 A / 14.0 V
Current Range	10 – 200 A
Operating Temperature	-10 to +40 °C (+14 to +104 °F)
Enclosure Class	IP23S
Certification Mark	CSA
Dimensions	403 x 153 x 264 mm (15.7 x 6 x 10.4 in.)
Weight	9.6 kg (21.2 lbs)

Ordering Information	
Rogue ET 200iP PRO CSA	0700500073

Package includes: power source with 3 m (10 ft) mains cable and plug, shoulder strap, TIG torch SR-B 26 type with flexible neck and potentiometer 4m (13 ft), a set of wear parts including tungsten electrode, SMAW electrode holder 3 m (10 ft), work lead with clamp 3 m (10 ft), gas regulator, power adapter 115V/230V.

Options & Accessories	
Shoulder strap	0700500086
MMA 4 Analogue Remote Control incl. 10 m (32 ft) cable and 8-pin connector	0700500084
TIG Torch SR-B 26 with Flexible Neck and Potentiometer 4 m (13 ft)	0700025557
TIG Torch SR-B 26 with Flexible Neck and Potentiometer 8 m (26 ft)	0700025591
Victor Argon Flow Gauge Regulator GF-250-50-580	0781-9411
Electrode Holder 200 A and Lead Assembly, 4 m (13 ft), 50 mm	WS200E13
Ground Clamp 200 A and Lead Assembly, 3 m (10 ft), 50 mm	WS200G10
TIG Foot Control, 4.5 m (15 ft) cable and 8-pin connector	W4014450



ESAB / esab.com

